

Product data sheet



Product	: Ellen Matic Primera	Page 1/2
Product group	: automatic draught excluders	
Description	: automatic draught excluder against draught , fire and smoke Smoke excluding according to DIN 18095. Fire retarding according to NEN 6069, T30	
Test Institutes:	Smoke excluding	- TNO (Holland)
	Fire retarding	- TNO (Holland)
Size	: Width 35 mm, Height 40 mm.	
Activation	: one side.	
Max. travel	: 12mm, individual installation	
Max. gap	: 10 mm	
Min. gap	: 5 mm	
Cutting Door	: not applicable	
without demounting door		
Mounting	: by wings at bottom door	
Application	: DIN R/L applicable	
Material	: aluminium	
Material seal	: PVC – EVFHSD	



Product data sheet

Product	: Ellen Matic Primera	Page 2/2
Standard Length	: 630, 730, 830, 930, 1030, 1130, 1230 mm	
Length alternatives	: between 200 – 629 mm (not to be cut, special production)	
Length alternatives	: 1231 – 1500 mm, single activation possible	
Length alternatives	: max. 1500 mm	
Required Length	: Door size	
To be cut	: at one sided activation 100 mm	
Fixed lengths	: Fixed lengths can not be shortened	
Mounting	: Groove 17 x 39 mm	
Accessories	: 2 plates and screws to mount.	
Specialties	:	
Door types	: Wooden inner and outer doors	



Elton BV Postbus 5 NL-9300AA Roden
Tel 0031 (0)50- 5021199 Fax 0031 (0)50 50 14772 E mail ellen@elton.nl